

## **PC Hardware Requirements**

DSX, DSX-SQL, PC Master, L85 and SIO are compatible with the latest and most recent Windows Platforms. PC Hardware and Operating Systems for these applications are outlined below. The hardware requirements are a minimum specification, which can always be exceeded if desired. All PCs used in the DSX system <u>must meet these minimum requirements</u> for the system to be supported by DSX.

Note /// System performance is dependent on the PC and LAN processing speed. If you have any questions regarding the DSX software and PC requirements, please call DSX Technical Support.

CPUs Minimums	Application
Pentium 2.8 GHz Dual Core	Host PC for single PC, single
(or better)	location system, or LAN
	workstation for single
	location system. 4G RAM
Pentium 2.8 GHz (or better)	LAN Comm Server or File
	Server for single location
	system, or workstation for
	multi-location system.
	4G RAM
Pentium 2.8 GHz Dual Core	LAN Comm Server and/or
(or better)	combination File Server for
	multi-location system.
	8G RAM - minimum
Memory Minimums	Application
4G	Basic System, Single PC
4-84G+	Multi-Location Comm Server
	and Badging
Drive Minimums	Application
USB Port for Flash Drive	Software Installation
1G Hard Drive Space	Basic System requires 50M
minimum	
Monitor	Application
SVGA 800 x 600 or better	Badging, Maps
65,000 colors or better	
17" or larger recommended	

I AN Communications	
LAN Communications	10075
Adapter 100Mbit or better	100M or better recommended
	Use MS Loopback Address
Requires TCP/IP Protocol	if there is no LAN
Comm Server	Static IP Address -required
LAN Modules	Static IP Address -required
Comm Server to Controller	UDP - ports 4000 to 5000
Comm Server to Workstation	TCP - ports 22223 / 22224
	•
Sound	Application
Windows <sup>TM</sup> compatible	DSX can play WAV files for
sound card.	input alarms.
Sound card.	mput ululiis.
Backup Gear	Application
Васкир Сеаг	
W: d TM 4:1.1.	DSX can send backups to
Windows <sup>™</sup> compatible	logical drive. DSX SQL uses
Backup gear.	SQL Server for backups.
Modem	
DSX External dial-up	DSX Modems are the only
	modems supported by DSX.
Serial Ports	
DSX-USB – USB to RS-232	Direct and Dialup
/ RS-485.	communications require a
	serial port.
Client Operating Systems	DSX Version
Windows <sup>TM</sup> 10 Pro +64 bit	3.10.11 / 4.10.11 and higher
Windows <sup>TM</sup> 8.1 Pro +64 bit	3.7.154 / 4.8.114 and higher
Windows <sup>TM</sup> 7 Pro + 64 bit	3.7.152 / 4.8.112 and higher
	3.7.132 / 4.8.112 and migher
The Comm Server Program	
can run on a Client Operating	
System.	
Server Operating Systems	
Server 2008 R2	3.7.152 / 4.8.112 and higher
Server 2012 R2	3.9 / 4.9 and higher
Server 2014	3.9 / 4.9 and higher
Server Operating Systems	
require Active Directory.	
SQL Server	
SQL 2005	DSX SQL requires Microsoft
Syc Pack 3	SQL Server. DSX uses
SVC I dek J	Microsoft Access.
SOI 2008	
SQL 2008 P2 + (41-)4	3.7 / 4.7 and higher
SQL 2008 R2 +64bit	3.7 / 4.7 and higher
SQL 2012 R2 +64bit	*additional configuration
SQL 2014	*additional configuration
Dependencies	.NET Framework 4.0 or >
Comm Server	For DSX Key Monitor.exe
Client Workstation	For WebCam, Email/Text
Choir (Chombation	202 11 00 Cum, Emun 1 Ont
	i .